



*shown with WhisperKOOL carbon panel

Key Features

- Through-the-wall installation
- Condensate evaporator
- Two-speed fan switch
- Up to 45% more capacity
- UV light upgrade
- Customizable front panel
- Strategic relocation of internal components
- Liquid temperature measuring bottle probe
- Can be mounted above a door
- 30°F temperature differential

Features

We are happy to announce the first unit in our new luxury series (LS). The new Slimline LS has evolved into a unit that can cool at two capacities at the flip of a switch. We have added centrifugal blowers, which are significantly quieter and can also be set at a medium or low speed, larger coils for greater system capacity, and an improved condensate management system. The controller has been moved to the condenser side of the unit for easy access. We offer a UV light upgrade to protect your unit from mold and an interchangeable decorative grille to customize the look of your luxury system.

Specifications

Fan Speed	Low	Medium
Cellar Size	650 cu. ft.*	1000 cu. ft.*
BTU/h (60°F condenser air intake temperature)	2601/1961 (total/sensible)	3032/2413 (total/sensible)
BTU/h (75°F condenser air intake temperature)	2635/1951 (total/sensible)	2904/2309 (total/sensible)
BTU/h (85°F condenser air intake temperature)	2396/1870 (total/sensible)	2612/2158 (total/sensible)
BTU/h (95°F condenser air intake temperature)	2205/1704 (total/sensible)	2392/2008 (total/sensible)
CFM	81	111
Dimensions	21.5"L x 22.16"W x 10.33"H	
Refrigerant	R-134a	
HP	1/5	
Voltage Rating	115V (20 amp dedicated circuit required); 230V (subject to availability)	
Weight (lbs)	81 lbs. without packaging, 90 lbs. with packaging	
Amps	4.3 (running amps)	
Drain Line	1/2" ID clear plastic tubing (not provided)	
Installation	Through the wall, ideally above a doorway	
Thermostat	Advanced digital display, liquid-temperature-measuring bottle probe (retractable cable)	
Temp. Delta	Can maintain a 55°F cellar temperature with up to 85°F condenser air intake temperature	
Warranty	Two-year limited warranty (parts and labor) / Five-year limited warranty (compressor)	

*Approximated in an environment that is fully insulated and sealed with a proper vapor barrier. Each wine cellar is unique and has specific cooling requirements.

Heat load calculations should always be performed prior to selecting a cooling unit.

